

Wilden T8 - 51 mm (2") Metal Pump Specifications

Introducing Wilden T8 - 51 mm (2") Metal Pump: Exclusive Distribution by Altools Services

Altools Services is proud to be the sole distributor of the renowned Wilden T8 - 51 mm (2") Metal Pump. This diaphragm pump is a high-performance, positive displacement pump designed to handle a variety of fluids with efficiency and reliability.

Key Features:

High Flow Rate: Up to 617.0 LPM (163 GPM)

Maximum Pressure: 8.6 BAR (125 PSI)

Versatile Wetted Housings: Available in Aluminum and Cast Iron

Robust Non-Wetted Housings: Constructed from durable materials like Aluminum and Brass

Superior Suction Lift: 6.4 m (21') Dry, 9.5 m (31') Wet

Handles Solids: Maximum diameter of 6mm (1/4")

Variety of Elastomer Options: Suitable for various temperature ranges

Technical Specifications:

Flow Rate: 617.0 LPM (163 GPM)

Maximum Pressure: 8.6 BAR (125 PSI)

Wetted Housings:

Aluminum: 33.1 kg (72.0 lbs)

Cast Iron: 52.4 kg (114.0 lbs)

Non-Wetted Housings:

Center Block: Aluminum

Air Valve: Brass

Maximum Suction Lift Capability:

Wilden T8 - 51 mm (2") Metal Pump Specifications

Dry: 6.4 m (21')

Wet: 9.5 m (31')

Maximum Diameter Solids: 6mm (1/4")

Elastomer Options and Temperature Limits:

Buna-N: -12.2°C to +65.6°C (+10°F to +150°F)

Neoprene: -17.8°C to +93.3°C (0°F to +200°F)

EPDM: -51.1°C to +137.8°C (-60°F to +280°F)

Polyurethane: -12.2°C to +65.6°C (+10°F to +150°F)

Saniflex: -28.9°C to +104.4°C (+20°F to +220°F)

PTFE: +4.4°C to +104.4°C (+40°F to +220°F)

Viton: -40°C to +176.7°C (-40°F to +350°F)

Wil-Flex: -40°C to +107.2°C (-40°F to +225°F)

Applications:

Chemical processing

Food and beverage industry

Pharmaceutical manufacturing

Wastewater treatment

Mining operations

Oil and gas industry

General industrial use

Keywords:

Wilden T8 - 51 mm (2") Metal Pump Specifications

Wilden T8 Pump

Diaphragm Pump

Positive Displacement Pump

Fluid Handling

Industrial Pump

Chemical Pump

Wastewater Pump

Mining Pump

Oil and Gas Pump

Altools Services

Tags:

#WildenT8 #DiaphragmPump #PositiveDisplacementPump #FluidHandling #IndustrialPump

#ChemicalPump #WastewaterPump #MiningPump #OilAndGasPump #AltoolsServices

For More Information:

For more information or to place an order, contact Altools Services at <https://Altools.ng> or visit <http://lystus.com.ng>, the exclusive distributor of Wilden pumps, and ensure your operations benefit from the best in pumping technology.

Weight and Dimensions:

Weight:

Aluminum: 33.1 kg (72.0 lbs)

Cast Iron: 52.4 kg (114.0 lbs)

Wilden T8 - 51 mm (2") Metal Pump Specifications

Dimensions: [Please provide the specific dimensions if needed]